



# PACKAGE PAVEMENT™ ALL-WEATHER™ BLACKTOP PATCH

**1. Product Name:** ALL-WEATHER BLACKTOP PATCH

**2. Item Codes:**

- 102240 - (40 LB. - 80 Bags / Pallet)
- 102306 - (60 LB. - 56 Bags / Pallet)
- 102200 - (80 LB. - 35 Bags / Pallet)

**3. Manufacturer:**

Package Pavement Co., Inc.  
675 Leetown Road, PO Box 408  
Stormville, NY 12582  
(800) 724-8193  
FAX (845) 221-0433  
www.packagepavement.com

**4. Product Description:**

PACKAGE PAVEMENT All-Weather Blacktop patch is a specially blended mix of high quality asphalt and 1/4" aggregate used for patching potholes and cracks greater than 1" wide in asphalt pavement. It is suitable to use for patching potholes in roads, driveways and walkways. Can also be used to repair drainage grates, and creating build-up ramps for garage entrances. Ready-to-Use straight from the bag. Requires no heating, mixing, or additions. Patched surfaces are ready for immediate foot traffic after application. Once thoroughly compacted shrinkage or expansion of the patch is eliminated.

**5. Technical Data:**

Complete installation instructions can be found on the PACKAGE PAVEMENT BLACKTOP PATCH bag. Product is designed for surface repair only.

<b>All-Weather Bag Yields:</b>	40 LB. BAG = 4 s.f.
	60 LB. BAG = 5 s.f.
	80 LB. BAG = 6.5 s.f.

**6. Installation:**

Installation of PACKAGE PAVEMENT ALL-WEATHER BLACKTOP PATCH can be done in **3 EASY STEPS...**

**1 > CLEAN**

Sweep and clean area to be filled. Square off the edges of the hole and remove all loose material. Vertical sides will provide a stronger patch.

**2 > FILL**

Apply at least 1" thick, compacting each 1/2" layer. Fill the hole to a height of 1/2" above the surrounding surface. Patches over 1" thick must be applied in 1/2" lifts which must be adequately compacted before additional material is added.

**3 > COMPACT**

Compact the area with a roller or tamper. The patch may also be covered with plywood or plastic and driven over to increase compaction.



**7. Caution:**

Avoid getting PACKAGE PAVEMENT Blacktop Patch on hands or clothing. For patching use only. Not for use as a blacktop pavement resurfacer. Avoid turning car tires over patch until surface cures. (Appx. 2-3 Days depending on weather conditions.)

**PLEASE READ BEFORE USING**

This mixture contains petroleum distillates which can be injurious if inhaled. Contains petroleum asphalt which is listed as a potential carcinogen by IARC. Store the container in a well ventilated area. Do not breathe fumes excessively or expose to an open flame. Avoid eye contact or prolonged contact with skin. Wash skin thoroughly with water after handling. In case of eye contact, wash with plenty of water for at least 15 minutes. If irritation persists, consult a physician immediately.

**8. Safety and Handling:**

Always wear gloves when handling and avoid contact with eyes or mouth. If the product comes in contact with eyes, rinse them thoroughly with water.

**9. Winter/Summer Asphalt Changes:**

To enable peak performance year round, PACKAGE PAVEMENT modifies the asphalt blend to keep the liquid attuned to the season. To ensure that your stock is designed for the current season, rotate it on a regular basis.

**KEEP OUT OF REACH OF CHILDREN**

**10. Warranty:**

Package Pavement warrants this product to be of merchantable quality when used or applied in accordance with the instructions herein. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is LIMITED to the replacement of this product (as purchased) found to be defective or, at the shipping company's option, to a refund of the purchase price. In the event of a claim under this warranty, notice must be given to Package Pavement in writing. This limited warranty is issued and accepted in lieu of all other express warranties and excludes liability for consequential damages.

ASPHALT PRODUCT SPECS